



Sealant / Filler

Bostik Fill-A-Gap - Acrylic

Code	Size	Colour	Box Qty
G04 MGF	450 gr	White	20

Uses: Sealing Cracks in plasterboard, skirting, architraves, brickwork, concrete and light partition walls,
 Sealing windows and door frames, around ceramic tiles,
 Crack filling prior to painting

Features: Fast drying, sandable, non sag and water resistant when cured
 Can be painted over in 2 hours, is fungus and mould resistant and has acoustic properties.



H.B.Fuller

Caulking Compound - Acrylic

Code	Size	Colour	Box Qty
G04 FCCWHITE	450 gr	White	6
G04 FCCBRWHITE	450 gr	Brilliant White	6
G04 FCC LITEIVORY	450 gr	Light Ivory	6
G04 FCCVANILLA	450 gr	Vanilla	6
G04 FCCMOCCA	450 gr	Mocca	6
G04 FCCCREAM	450 gr	Cream	6
G04 FCCTERACOTA	450 gr	Terracotta	6
G04 FCCCEDAR	450 gr	Cedar	6
G04 FCCLIGHTGREY	450 gr	Light Grey	6
G04 FCCCHARCOAL	450 gr	Charcoal	6
G04 FCCBLACK	450 gr	Black	6

Uses: Sealing wet areas where immersion does not occur, filling gaps between baths, basins, shower hobs and tiles, expansion joints in brickwork and tiled walls, architraves, windows and door frames, expansion joints around the perimeter of timber windows.

Features: Dries 'true' to wet colour, won't crack, peel or split over time, good for horizontal and vertical applications, flexible: +/- 20% joint movement capability, mould and mildew resistant





Sealant / Filler

Fire Rated Acoustic Sealant

Code	Size	Colour		Box Qty
G17 FFSGREY	450 gr	Grey	Cartridge	20
G17 FFSSGREY	600 gr	Grey	Sausage	15

Uses: Sealing exterior and interior construction joints that are subject to movement in pre-cast concrete panels, blockwork and brickwork
 Sealing gaps around cables, metal pipes, conduits, busways and ducts that penetrate walls, floors and ceilings.
 If joint movement is not required, this sealant can be used as a putty for filling fire rated substances.



Features: Fire rating for gaps up to 50mm, excellent acoustic properties, Up to 4 hour fire rating (AS1530.4-1990) it is paintable and flexibility of +/- 20% joint movement capability, intumescent; expands when exposed to fire or heat above 90 degrees C

Polyurethane Sealant

Code	Size	Colour		Box Qty
G04 FHPR25BLACK	400 gr	Black		12
G04 FHPR25WHITE	400 gr	White	Cartridge	12
G04 FHPR25GREY	400 gr	Grey		12

Uses: Sealing expansion and control joints in walls, tiling, roofs, door and window perimeters, cladding and brickwork.
 Applications where a level of chemical resistance is required.
 In seals where acoustic properties are required.



Features: Fast skinning, Highly flexible +/- 25% joint movement capability.
 Low modulus, Isocyanate and solvent free, Non gassing.
 Excellent weather and UV resistance, resists yellowing.
 Does not sag or slump in joints up to 30mm

G04 FSS#101BLACK	600 ml	Black		20
G04 FSS#101WHITE	600 ml	White		20
G04 FSS#101PRECA	600 ml	Pre - Cast	Sausage	20
G04 FSS#101GREY	600 ml	Grey		20

Uses: Sealing expansion and control joints in walls, tiling, roofs, door and window perimeters, cladding and brickwork.
 Applications where a level of chemical resistance is required.
 In seals where acoustic properties are required.

Features: Fast skinning, Highly flexible +/- 25% joint movement capability.
 Low modulus, Isocyanate and solvent free, Non gassing.
 Excellent weather and UV resistance, resists yellowing.
 Does not sag or slump in joints up to 30mm

Sealant / Filler

Expanding Foam

Code	Size		Box Qty
G28 SF600	500 ml	Paintable	12
G28 SF750	750 ml		12



Water Proofing Membrane

Code	Size		Box Qty
G18 WPM30004	4 lt		12
G18 WPM30020	20 lt		12

